






**Process for reducing the measuring cycle time and for increasing the measuring pressure sensitivity of a leak-testing method, and associated test container.**





**Publication number:** EP0379986  
**Publication date:** 1990-08-01  
**Inventor:** LEHMANN MARTIN (CH)  
**Applicant:** LEHMANN MARTIN (CH)  
**Classification:**  
- **International:** G01M3/32; G01M3/32; (IPC1-7): G01M3/32  
- **European:** G01M3/32E2  
**Application number:** EP19900101074 19900119  
**Priority number(s):** DE19893902435 19890127

**Also published as:**

 US5042291 (A1)  
 JP2232543 (A)  
 JP11218462 (A)  
 EP0379986 (A3)  
 DE3902435 (A1)

more &gt;&gt;

**Cited documents:**

 US3177704  
 US3517548  
 CH395584  
 JP58034337

**Report a data error he****Abstract of EP0379986**

In order to define as small an intermediate volume (V Z) as possible for the leakage test of receptacles (3), the cross-sectional area of which narrows in one direction, by applying a pressure difference between a test chamber and the interior of the receptacles (3), the test chamber has a case (39) likewise narrow like the receptacle (3) to be tested, a closure lid in the opening region (41) and also an ejection piston (4) at the base part. In addition, an outflow line (49) for flushing agent is closed in a sealing manner or opened by means of the piston (47).

---

Data supplied from the **esp@cenet** database - Worldwide